Our Solar Grid –Tie with Battery Backup

Presented at the Bowen Island Solar Power Forum , 4 Apr. 2016

Phil Gregory (gregory@phas.ubc.ca)

Solar Electricity Options

1) Off grid.
   - Need a battery to store excess power production and use at night.

2) Grid tie with no battery. (very efficient > 95%)
   - Use the grid as a very efficient storage battery to store your excess.
   - Not able to produce any power when the grid goes down.

3) Grid tie with battery.
   - Still have power when the electricity grid is down.
   - Overall efficiency converting solar energy from my panels to 220/120 V AC: **68% in summer, 45% in winter**

Our 3.9 kW system provides 20% of our electrical power

Phil Gregory's Solar Power

Feb. 2015

Solar Modules

↓

DC to DC converter

↓

24 V Battery

↓

4 kW Inverter/charger

↓

220 V AC Electrical & Intranet connection to house




DIRECTORY / DIRECTOIRE
HOT WATER
HOUSE EXTENSION SUB PANEL
EATON


HYDRO
MAIN ELECTRICAL
STOVE
HOT WATER
HEATER
DRYER
TV
COMPUTERS
INTERNET
SUB PANEL
WASHER
REFRIGERATOR
FREEZER
WELL PUMP
SOLAR SHED
INVERTER & CHARGER
24 V BATTERY BANK
SOLAR PANELS
BATTERY CHARGER

Costs

First phase 2008 (8 x 200 W panels = 1600 W)

8 Sanyo panels ($5.85 per W)	=	$9368
Xantrex 4 kW 120/240 W Inverter/Charge	=	$4873
Control panel + charge controller + gateway	=	$2086
Mounting rails	=	$ 980
Batteries (24 V, 24 kWh capacity) + shipping	=	$5343 ($6555 in 2016)
Labour + electrical supplies + safety permit +GST	=	$8205
Phase 1 total ----------	=	$30,855

Second phase 2015 (9 x 260 W panels = 2340 W)

9+1 spare Canadian Solar panels ($0.94 per W)	=	$2440
Mounting rails	=	$ 615
2 charge controllers	=	$1502
Electrical supplies + safety permit ($239)	=	$ 912
Labour + travel	=	$1373
GST	=	$ 263
Phase 1 total ----------	=	$ 7,105

Total ---------- = $37,960

Estimated cost of my system today

3900 W grid tie with battery

15 x 260 W panels = 3900 W ($1 per W)	=	$3900
4 kW 120/240 W Inverter/Charge	=	$3500
Control panel + 3 charge controllers + gateway	=	$3600
Mounting rails	=	$1200
Batteries (24 V, 24 kWh capacity) + shipping	=	$6555
Labour + electrical supplies + safety permit +GST	=	$10000
Total ----------	=	$25,155

Cost per W = $6.45

3900 W grid tie NO battery

15 x 260 W panels = 3900 W ($1 per W)	=	$3900
8 micro-inverters	=	$2300
Monitoring unit	=	$ 600
Mounting rails	=	$1200
Labour + electrical supplies + safety permit +GST	=	$5000
Total ----------	=	$13,000

Cost per W = $3.34

Battery life issues



A Comparison of Lead Acid and Lithium-ion in Stationary Storage Application, Greg Albright, Jake Edie, Said Al-Hallaj , AltEnergyMag , 2012, http://www.altenergymag.com/content.php?post_type=1884

Bowen Island power outages

Typical significant power outage duration = 8 hr
Average load during outage = 0.4 kW
Battery discharge = 8 x 0.4 = 3.2 kWh
My battery rated at 24 kWh

Battery discharge for an 8 hr outage = 24 %

Tesla Powerwall Li-ion batteries

Advertise 6.4 kWh units for $3500 US or $4500 CAD

$16900 CAD to replace my 24 kWh battery capacity. That's 2.6 times the cost of lead acid but because Li-ion can be more deeply cycled for a similar or longer lifetime, one could probably get by with a smaller battery capacity.

Advantages: 92% efficiency, no maintenance, more environmentally friendly to produce

Disadvantage: The likelihood and consequences of a thermal runaway event are higher for lithium-ion. It has a higher amount of energy in a smaller volume. On the other hand a flooded lead acid batteries produce hydrogen gas which needs to be vented for safe operation.

Comparison of daily energy produced by the solar modules (at output of DC to DC converters) compared to AC energy emerging from the inverter



Efficiency of solar energy conversion measured from the output of the DC to DC converters through to the inverter AC output for my grid tie battery system



Charge Controller (DC to DC converter) Efficiencies





A charge controller, also known as a DC to DC converter, transforms the solar module output voltage to the voltage required to charge the battery.



My system of mounting the panels on wooden T beams provides good airflow below the panels, leading to lower panel temperature operation for greater energy output.